

# TECHNICAL DATASHEET




## EF TAPPING SADDLE

04 Update - 01/2023

### TECHNICAL DATA

Article No	001 117 2071 0134
d (mm)	125
d1 (mm)	20
le (mm)	75
h (mm)	212
h1 (mm)	82
Z (mm)	120
L (mm)	140
Weight (Kg)	0,700
Box Quantity (pcs)	8
Box Dimension (cm)	55x30x36

### INJECTION MOULDED



### IDENTIFICATION OF PRODUCT

D(mm)	125-20
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3

SPECIFICATION	Suitable for SDR11....17 pipe
	Injected monobloc type
	4 mm pin connectors
	Long Fusion outlet
	Hexagon wrench 17 mm
	O-ring sealed screw cap

### EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	7,0 $\Omega$
WELDING TIME	140 Sec.
COOLING TIME	15 Min.
WINDING TYPE	Monofilar
WELDING BARCODE	



Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance  $\pm 5\%$ . NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.