


FLANGE ADAPTOR

03 Update - 06/2022

TECHNICAL DATA

| | |
|------------------------|-------------------|
| Article No | 001 117 0103 0063 |
| d (mm) | 63 |
| d1 (mm) | 78 |
| d2 (mm) | 100 |
| d3 (mm) | |
| le (mm) | 88 |
| L (mm) | 14 |
| Z (mm) | 120 |
| s (mm) | 5,8 |
| Weight (Kg) | 0,190 |
| Box Quantity (pcs) | 60 |
| Box Dimension (pcs) | 55x30x42 |

INJECTION MOULDED



IDENTIFICATION OF PRODUCT

| | |
|----------------|---|
| D(mm) | 63 |
| SDR | 11 |
| RAW METARIAL | PE 100 |
| PRESSURE CLASS | 16 Bar Water 10 Bar Gas |
| TRADEMARK | NTG |
| EXECUTION | Injection Moulded |
| STANDARD | EN 12201-3 EN 1555-3 AS /NZS 4129 |

SPECIFICATION

Long Spigot
Suitable for butterfly valve
Suitable for ansi flange
Chamfered finish, where d3 size is given

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance $\pm 5\%$. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.

Fr 161 Rev 00