



BACKING FLANGE, PP STEEL (ANSI)

PP %30 Glass-fibre reinforced with steel ring
UV-resistant suitable for outdoor use

Connecting Dimension

ANSI ASME B16,5 class 150
ASTM D4024
BS EN 1759

Bolt circle class 150

d	DN	Article No	D	a	k	b	l	Bolt	Hole Qty.	Weight	Box	
mm	mm	inch	mm	mm	mm	mm	mm	mm	mm	kg	pcs	
20	15	1/2"	001 530 7121 0020	95	28	60,5	12	16	M12	4	0,210	56
25	20	3/4"	001 530 7121 0025	102	34	69,9	12	16	M12	4	0,235	48
32	25	1"	001 530 7121 0032	114	42	79,3	16	16	M12	4	0,475	25
40	32	1 1/2"	001 530 7121 0040	130	51	88,9	16	16	M12	4	0,670	18
50	40	1 1/2"	001 530 7121 0050	133	62	98,6	18	16	M12	4	0,610	15
63	50	2"	001 530 7121 0063	165	78	120,6	18	20	M16	4	1,020	12
75	65	2 1/2"	001 530 7121 0075	184	92	139,7	18	20	M16	4	1,290	8
90	80	3"	001 530 7121 0090	194	111	152,4	20	20	M16	4	1,450	7
110	100	4"	001 530 7121 0110	229	133	190,5	20	20	M16	8	1,935	7
160	150	6"	001 530 7121 0160	283	178	241,3	24	22	M20	8	3,935	4
180	150	6"	001 530 7121 0180	285	188	241,3	24	22	M20	8	3,330	4
200	200	8"	001 530 7121 0200	345	236	298,5	27	22	M20	8	5,090	2
250	250	10"	001 530 7121 0250	412	288	361,9	32	32	M22	12	9,780	1
315	300	12"	001 530 7121 0315	487	338	431,8	32	25	M22	12	14,410	1
355	350	14"	001 530 7121 0355	533	376	476,2	42	28,5	M27	12	24,750	1
400	400	16"	001 530 7121 0400	596	430	539,7	44	28,5	M27	16	31,470	1