

# TECHNICAL DATASHEET




## EF COUPLER

04 Update - 04/2024

### TECHNICAL DATA

Article No	001 115 2160 0250
d (mm)	250
D (mm)	288
Z (mm)	228
m (mm)	54
Weight (Kg)	3,619
Box Quantity (pcs)	4
Box Dimension (cm)	36x60x46,5

### INJECTION MOULDED



### IDENTIFICATION OF PRODUCT

D(mm)	250
SDR	17
RAW MATERIAL	PE 100
PRESSURE CLASS	10 Bar Water 6 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3 EN 1555-3 AS / NZS 4129
SPECIFICATION	Suitable for SDR17...26 pipe 4 mm pin connectors

### EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	0.65 $\Omega$
WELDING TIME	450 Sec.
COOLING TIME	30 Min.
WINDING TYPE	Monofilar
WELDING BARCODE	

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance  $\pm 5\%$ . NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.