

# TECHNICAL DATASHEET




## EF REDUCER

03 Update - 01/2024

### TECHNICAL DATA

Article No	001 117 2080 0034
d1 (mm)	32
d2 (mm)	20
D1 (mm)	44
D2 (mm)	32
le1 (mm)	48
le2 (mm)	32
Z (mm)	85
m1 (mm)	27,4
m2 (mm)	14,2
Weight (Kg)	0,062
Box Quantity (pcs)	75
Box Dimension (cm)	35,5x35,5x27,5

### INJECTION MOULDED



### IDENTIFICATION OF PRODUCT

D(mm)	32-20
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3 EN 1555-3 AS / NZS 4129

SPECIFICATION	Suitable for SDR9...11 pipe 4 mm pin connectors
---------------	--

### EF SPECIFICATION

WELDING VOLTAGE	40V
RESISTANCE	3,82 $\Omega$
WELDING TIME	25 Sec.
COOLING TIME	5 Min.
WINDING TYPE	Monofilar
WELDING BARCODE	



931420300623403824025113

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance  $\pm 5\%$ . NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.