


EF TAPPING SADDLE

04 Update - 05/2024

TECHNICAL DATA

Article No	001 117 2071 0054
d (mm)	50
d1 (mm)	20
le (mm)	64
h (mm)	135
h1 (mm)	43
Z (mm)	105
L (mm)	120
Weight (Kg)	0,300
Box Quantity (pcs)	30
Box Dimension (cm)	55x30x37,5

INJECTION MOULDED



IDENTIFICATION OF PRODUCT

D(mm)	50-20
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3 EN 1555-3 AS / NZS 4129

EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	10,5 Ω
WELDING TIME	45 Sec.
COOLING TIME	10 Min.
WINDING TYPE	Monofilar

WELDING BARCODE



941420311242401055045119

SPECIFICATION

Suitable for SDR11 pipe
 Injected monobloc type
 4 mm pin connectors
 Long Fusion outlet
 Hexagon wrench 12 mm
 O-ring sealed screw cap

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance $\pm 5\%$. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.