


## EF TAPPING SADDLE

04 Update - 05/2024

### TECHNICAL DATA

Article No	001 117 2071 0052
d (mm)	50
d1 (mm)	32
le (mm)	76
h (mm)	135
h1 (mm)	43
Z (mm)	117
L (mm)	120
Weight (Kg)	0,330
Box Quantity (pcs)	30
Box Dimension (cm)	55x30x37,5

### INJECTION MOULDED



### IDENTIFICATION OF PRODUCT

D(mm)	50-32
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3 EN 1555-3 AS / NZS 4129

### SPECIFICATION

Suitable for SDR11 pipe  
 Injected monobloc type  
 4 mm pin connectors  
 Long Fusion outlet  
 Hexagon wrench 12 mm  
 O-ring sealed screw cap

### EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	10,52 Ω
WELDING TIME	45 Sec.
COOLING TIME	10 Min.
WINDING TYPE	Monofilar
WELDING BARCODE	



941420311262401055045113

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance  $\pm 5\%$ . NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.