

TECHNICAL DATASHEET




EF REDUCED TEE 90°

04 Update - 04/2024

TECHNICAL DATA

Article No	001 117 2042 0051
d1 (mm)	50
d2 (mm)	40
D (mm)	64
Z (mm)	138
L (mm)	89
le1 (mm)	43
le2 (mm)	52
m (mm)	24
Weight (Kg)	0,222
Box Quantity (pcs)	10
Box Dimension (cm)	27,5x24x24,5

INJECTION MOULDED



IDENTIFICATION OF PRODUCT

D(mm)	50-40
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3 EN 1555-3 AS / NZS 4129

SPECIFICATION	Suitable for SDR9...11 pipe 4 mm pin connectors
---------------	--

EF SPECIFICATION

WELDING VOLTAGE	40V
RESISTANCE	2,85 Ω
WELDING TIME	60 Sec.
COOLING TIME	10 Min.
WINDING TYPE	Monofilar
WELDING BARCODE	



971420310503402856060118

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance $\pm 5\%$. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.