

# TECHNICAL DATASHEET




## EF REDUCER

03 Update - 01/2024

### TECHNICAL DATA

Article No	001 117 2080 0051
d1 (mm)	50
d2 (mm)	40
D1 (mm)	62
D2 (mm)	53
le1 (mm)	61
le2 (mm)	57
Z (mm)	124
m1 (mm)	28
m2 (mm)	22
Weight (Kg)	0,130
Box Quantity (pcs)	80
Box Dimension (cm)	55x30x37,5

### INJECTION MOULDED



### IDENTIFICATION OF PRODUCT

D(mm)	50-40
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3 EN 1555-3 AS / NZS 4129

### EF SPECIFICATION

WELDING VOLTAGE	40V
RESISTANCE	0,95 Ω
WELDING TIME	30 Sec.
COOLING TIME	5 Min.
WINDING TYPE	Monofilar
WELDING BARCODE	



SPECIFICATION	Suitable for SDR9...11 pipe 4 mm pin connectors
---------------	--

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance ± 5%. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.