

# TECHNICAL DATASHEET




## EF COUPLER

04 Update - 02/2023

### TECHNICAL DATA

Article No	001 117 2160 0063
d (mm)	63
D (mm)	82
Z (mm)	106
m (mm)	25,6
Weight (Kg)	0,204
Box Quantity (pcs)	36
Box Dimension (cm)	35,5x35,5x26

### INJECTION MOULDED



### IDENTIFICATION OF PRODUCT

D(mm)	63
SDR	11
RAW MATERIAL	PE 100
PRESSURE CLASS	16 Bar Water 10 Bar Gas
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3

### SPECIFICATION

EN 1555-3  
AS / NZS 4129  
Suitable for SDR9...11 pipe  
Removable center stopper ( up to 400 mm )  
4 mm pin connectors

### EF SPECIFICATION

WELDING VOLTAGE	40 V
RESISTANCE	1,00 $\Omega$
WELDING TIME	48 Sec.
COOLING TIME	10 Min.
WINDING TYPE	Monofilar
WELDING BARCODE	



951420310633401006048114

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance  $\pm 5\%$ . NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.