

TECHNICAL DATASHEET




STEP REDUCER

01 Update - 12/2018

TECHNICAL DATA

Article No	001 117 1081 0633		
D1 (mm)	450	S1 (mm)	40.9
D2 (mm)	500	S2 (mm)	45.5
D3 (mm)	560	S3 (mm)	50.8
D4 (mm)	630	S4 (mm)	57.2
L1 (mm)	36	Z (mm)	200
L2 (mm)	36	Weight (Kg)	19.3
L3 (mm)	36	Box Quantity (pcs)	1
L4 (mm)	72	Box Dimension (pcs)	

INJECTION MOULDED



IDENTIFICATION OF PRODUCT

D(mm)	630-450
SDR	11
RAW METARIAL	PE 100
PRESSURE CLASS	16 Bar Water
TRADEMARK	NTG
EXECUTION	Injection Moulded
STANDARD	EN 12201-3 EN 1555-3 AS /NZS 4129

SPECIFICATION

Short Spigot
Special Equipment Required

Tolerance on diameters and thickness according to the standards. The other dimensions are specialized. Tolerance $\pm 5\%$. NTG PLASTIK reserves all the right to change any information without giving prior notice. The production, distribution and utilization of this document without explicit authorization is prohibited.

Fr 161 Rev 00